

102 **UNION GATE** (male union X female IPS)

| DIN | Approx. | | | |
|-------|---------|------|------|--------|
| SIZE | Α | В | С | Weight |
| 1/2 | 2.31 | 0.97 | 2.97 | 0.98 |
| 3/4 | 2.28 | 1.09 | 3.59 | 1.41 |
| 1 | 2.88 | 1.28 | 4.09 | 1.91 |
| 1 1/4 | 3.22 | 1.47 | 4.66 | 2.79 |
| 1 1/2 | 3.38 | 1.75 | 3.38 | 3.72 |

RATING

• FIG. 102 = 125 WSP & 200 WOG FIG. 108 = 15 WSP & 60 PSI NON-SHOCK HOT WATER (for low pressure steam and hot water) FIG. 201 = 60 PSI HOT WATER

FEATURES

- BRONZE BODY
- EPDM DISC
- PHENOLIC HAND-WHEEL (heat resistant)
- ADJUSTABLE PACKING NUT
- TAIL PIECE & UNION **NUT PART OF ASSEMBLY**
- 100% FACTORY TESTED
- INTERNATIONAL



108 **CONVECTOR STEAM ANGLE** (female union X female IPS)

| DIN | Approx. | | | |
|-------|---------|------|------|--------|
| SIZE | Α | В | С | Weight |
| 1 | 1.69 | 2.31 | 3.53 | 1.87 |
| 1 1/4 | 1.75 | 2.84 | 3.81 | 2.43 |



201 **CIRCULATOR ANGLE VALVE** (male union X sweat)

| DIM | Approx. | | | |
|------|---------|------|------|--------|
| SIZE | Α | В | C | Weight |
| 1/2 | 2.50 | 0.78 | 1.88 | 0.70 |
| 3/4 | 2.88 | 0.94 | 2.06 | 0.96 |

The information presented on this sheet is correct at time of publication. Hammond Valve reserves the right to change design and/or materials without notice. For our Installation, Operation and Maintenance Manual and the most current product information go to www.hammondvalve.com. Hammond Valve is a registered trademark of Milwaukee Valve.

