
125 WOG



DIMENSIONS (INCHES)					Approx. Weight	Approx. Weight
SIZE	Α	В	C	D	547	548
3/4 X 1/2	2.38	3.53	2.16	1.34	0.44	0.45
3/4 X 3/4	2.38	3.53	2.16	1.34	1.18	1.18
1 X 3/4	2.75	4.34	3.13	1.63	0.89	0.97
1 X 1	2.75	4.34	3.13	1.63	2.05	2.05

	MATERIAL SPECIFICATION					
1	Screw	Steel	Commercial			
2	Name Plate	Aluminum	Commercial			
3	Handwheel	Cast Iron	ASTM A126			
4	Packing Nut	Brass	ASTM B16			
5	Packing Gland	Buna	ASTM D2000			
6	Bonnet	Forged Brass	ASTM B124, C37700			
7	Stem	Brass	ASTM B16			
8	Body	Bronze	ASTM B584, C84400			
9	Seat	Buna	ASTM D2000			
10	Set Screw	Brass	ASTM B16			
11	Coupling	Bronze	ASTM B584, C84400			
12	Gasket	Buna	ASTM D2000			
13	Сар	Brass	ASTM B16			

RATING

• 225 PSI NON-SHOCK

FEATURES

- BRONZE BODY
- FLARED SOLDER END X THREADED
- THREADED BONNET
- ADJUSTABLE PACKING NUT
- RISING STEM
- BUNA DISC
- IRON HANDWHEEL
- 100% FACTORY TESTED
- DESIGNED FOR WATER METER APPLICATIONS
- INTERNATIONAL

The information presented on this sheet is correct at time of publication. Hammond Valve reserves the right to change design and/or materials without notice. For our Installation, Operation and Maintenance Manual and the most current product information go to www.hammondvalve.com. Hammond Valve is a registered trademark of Milwaukee Valve.

🛕 State of California Prop 65 WARNING: Cancer and Reproductive Harm. For more information visit www.p65warnings.ca.gov.

