



606 Threaded

607 Solder

DIMENSIONS (INCHES)				Approx. Weight 606	Approx. Weight 607
SIZE	A	B	D		
1/4	1.75	3.06	-	0.6	-
3/8	1.81	3.06	1.63	0.7	0.6
1/2	2.00	3.06	1.88	0.7	0.6
3/4	2.13	3.94	2.50	1.3	1.1
1	2.56	4.25	3.00	1.9	1.6
1 1/4	2.78	5.19	3.25	2.9	2.3
1 1/2	2.81	5.63	3.63	3.8	3.0
2	3.31	6.75	4.31	6.3	5.0
2 1/2 *	4.81	9.13	4.81	9.6	8.0
3 *	4.63	10.38	5.44	13.7	12.2

* These sizes with gland followers

MATERIAL SPECIFICATION			
1	Body	Cast Bronze	ASTM B584, C84400
2	Bonnet	Cast Bronze	ASTM B584, C84400
3	Disc	Cast Bronze	ASTM B584, C84400
4	Stem	Brass Rod	ASTM B16
5	Stuffing Nut	Brass Rod	ASTM B16
6	Handwheel Nut	Brass Rod	ASTM B16
7	Stem Retainer	Brass Rod	ASTM B16
8	Packing Ring	Non-Asbestos	
9	Handwheel	Malleable Iron	ASTM A-47
10	Nameplate	Aluminum Sheet	COMMERCIAL

RATING

- 125 PSI STEAM TO 353° F
- 200 PSI NON-SHOCK

FEATURES

- BRONZE BODY
- THREADED OR SOLDER ENDS
- THREADED BONNET
- ADJUSTABLE PACKING NUT
- INTEGRAL SEAT
- NON-RISING STEM
- SOLID WEDGE DISC
- MALLEABLE IRON HANDWHEEL
- 100% FACTORY TESTED

The information presented on this sheet is correct at time of publication. Hammond Valve reserves the right to change design and/or materials without notice. For our Installation, Operation and Maintenance Manual and the most current product information go to www.hammondvalve.com. Hammond Valve is a registered trademark of Milwaukee Valve.

⚠ State of California Prop 65 **WARNING:** Cancer and Reproductive Harm. For more information visit www.p65warnings.ca.gov.