## **BRASS HOSE END VALVES**

150 WWP



710*
BOILER DRAIN
(male IPS to hose)

DIM	Approx.			
SIZE	Α	В	С	Weight
1/2	1.56	3.50	2.13	0.45
3/4	1.56	3.63	2.13	0.46




Approx.

Weight 0.38

0.46

712*	DIMENSIONS (INCHES)				
/ 1 2	SIZE	Α	В	С	
BOILER DRAIN	1/2	3.00	2.22	2.09	
(female IPS to hose)	3/4	3.00	2.22	2.09	



1032	DIMENSIONS (INCHES)				Approx.
SILL FAUCET	SIZE	Α	В	С	Weight
(female IPS to hose)	1/2	2.44	2.75	2.00	0.42
(lemale IPS to hose)	3/4	2.44	2.75	2.00	0.43



1034	DIMENSIONS (INCHES)				Approx.
	SIZE	Α	В	С	Weight
SILL FAUCET	1/2	2.44	2.75	2.00	0.47
(solder to hose)	3/4	2.44	2.75	2.00	0.48

The information presented on this sheet is correct at time of publication. Hammond Valve reserves the right to change design and/or materials without notice. For our Installation, Operation and Maintenance Manual and the most current product information go to www.hammondvalve.com. Hammond Valve is a registered trademark of Milwaukee Valve. 🕅 State of California Prop 65 WARNING: Cancer and Reproductive Harm. For more information visit www.p65warnings.ca.gov.



PV-8

## RATING

 150 PSI WWP TO 200° F NON-SHOCK

## **FEATURES**

- BRASS BODY
- HEAVY DUTY PATTERN
- LARGE WATER WAY
- ADJUSTABLE **PACKING NUT &** STUFFING BOX
- BUNA-N- SEATS
- IRON HANDWHEEL
- HAMMOND NAME ON BODY
- 100% FACTORY TESTED
- INTERNATIONAL

\*User's are advised that some boiler applications require ASME code compliant and/or higher rated product, it is the user's responsibility to ensure all regulatory requirements are met for their installation.