




8301A/8303A* 1/4"-2"

**Bronze Ball Valve
Two Piece
Full Port
600 WOG/150 SWP (1)
Threaded Ends
Blow-Out Proof Stem
MSS SP-110**

MATERIALS LIST

| ITEM | PART | MATERIALS | ASTM SPEC. |
|------|---------------|------------------------------|------------|
| 1 | Body | Cast Bronze | B584 |
| 2 | Tailpiece | Brass | B283 |
| | | Cast Bronze (1 1/4" & up) | B584 |
| 3 | Ball | Brass w/Hard Chrome Plating | B16 |
| | | 316 Stainless Steel (B8303A) | A276 |
| 4 | Seat | RPTFE, 15% Glass Filled | |
| 5 | Stem | Brass | B16 |
| | | 316 Stainless Steel (8303A) | A276 |
| 6 | Thrust Washer | RPTFE, 25% Glass Filled | |
| 7 | Packing | PTFE | |
| 8 | Packing Nut | Brass | B16 |
| 9 | Handle | Steel w/Zinc Plating | Commercial |
| 10 | Hand Grip | Vinyl | |
| 11 | Handle Nut | Steel w/Zinc Plating | Commercial |

*Not intended for use in potable water.



DIMENSIONS

| | UNITS | 1/4" | 3/8" | 1/2" | 3/4" | 1" | 1-1/4" | 1-1/2" | 2" |
|---------|-------------|----------|----------|----------|----------|--------|------------|------------|--------|
| | | DN10 | DN10 | DN15 | DN20 | DN25 | DN32 | DN40 | DN50 |
| A (DIA) | INCHES | 0.38 | 0.38 | 0.50 | 0.76 | 1.06 | 1.31 | 1.56 | 2.00 |
| | mm | 10 | 10 | 13 | 19 | 27 | 33 | 40 | 51 |
| B | INCHES | 1.86 | 1.86 | 2.19 | 2.59 | 3.32 | 3.77 | 4.28 | 5.10 |
| | mm | 46 | 46 | 54 | 66 | 84 | 96 | 109 | 130 |
| C | INCHES | 1.00 | 1.00 | 1.10 | 1.30 | 1.59 | 1.81 | 2.06 | 2.37 |
| | mm | 25 | 25 | 27 | 33 | 40 | 46 | 52 | 60 |
| D | INCHES | 1.78 | 1.81 | 1.91 | 2.32 | 2.68 | 2.82 | 3.00 | 3.36 |
| | mm | 44 | 44 | 47 | 59 | 68 | 72 | 76 | 85 |
| E | INCHES | 3.82 | 3.82 | 3.82 | 4.55 | 6.33 | 6.33 | 6.33 | 7.19 |
| | mm | 94 | 94 | 94 | 116 | 161 | 161 | 161 | 183 |
| F | THREAD SIZE | 1/4" NPT | 3/8" NPT | 1/2" NPT | 3/4" NPT | 1" NPT | 1-1/4" NPT | 1-1/2" NPT | 2" NPT |
| Cv | | 7 | 7 | 13 | 30 | 61 | 110 | 185 | 360 |

Note: DN (Diameter Nominal) = Metric equivalent size.

The information presented on this sheet is correct at time of publication. Hammond Valve reserves the right to change design and/or materials without notice. For our Installation, Operation and Maintenance Manual and the most current product information go to www.hammondvalve.com. Hammond Valve is a registered trademark of Milwaukee Valve.

⚠ State of California Prop 65 **WARNING:** Cancer and Reproductive Harm. For more information visit www.p65warnings.ca.gov.

OPTIONS

8301A/8303A
8501/8503
8604/8603

16 THE INSULATOR/MS® Extension Handle


The **THE INSULATOR/MS®** extension handle is designed to prevent condensation and other extraneous moisture from entering the insulated piping system, while also minimizing thermal energy loss from the system via metal extension tubes, levers, and similar parts.



The design incorporates a unique memory stop feature that requires no disassembly or removal of the handle to engage and make adjustments.


07 Locking Device

The "07" Locking Handle offers the end user the security of a pad lockable handle. The handle can be locked in either the full open position, or full closed by adding a standard padlock. The locking handle design will accommodate a standard 5/16" pad-lock or other types of valve lockouts. The handle and locking device are also manufactured of stainless steel material for additional strength and corrosion resistance.




08 Stainless Steel Handle


The "08" handle option adds a 316 stainless steel handle and nut to a standard bronze ball valve. This option is intended for harsh environments like areas subject to salt water spray, high humidity, cleaning chemicals, etc.



04 Oval Handle




Oval handles can also prevent accidental valve operations, since they have less projection than a lever handle, and require more turning force to operate. OSHA requires the use of oval handles in many installations for safety reasons.




09 Extension Handle with Memory Stop

The "09" stem extension is all-metallic with an adjustable memory stop. This option is designed for installations where pipe insulation would make standard handles inoperable. The adjustable memory stop allows the valve opening to be limited to a preset position. This option can be ordered with or without the memory stop.



02 Memory Stop

The "02" Memory Stop offers the convenience of a preset stop when the valve is used in a balancing application. The memory stop can be set from the full closed position, to any preset opening point.




06 Extension Stem

The "06" stem extension is simple and effective design. This option is designed for installations where pipe insulation would make standard handles inoperable. The external plastic shield helps to keep the insulation away from the stem extension, providing years of trouble free operation.

03 Tee Handle

Tee handles offer the same installation space savings as oval handles, with a slightly shorter end to end dimension. Tee handles require more handle force to operate, so accidental openings can be reduced.



The information presented on this sheet is correct at time of publication. Hammond Valve reserves the right to change design and/or materials without notice. For our Installation, Operation and Maintenance Manual and the most current product information go to www.hammondvalve.com. Hammond Valve is a registered trademark of Milwaukee Valve.

⚠ State of California Prop 65 **WARNING:** Cancer and Reproductive Harm. For more information visit www.p65warnings.ca.gov.