8604/8603* P2 ½"-2"



Bronze Ball Valve
Three Piece
Full Port
200 psig @ 250°F†
Press x Press Ends
Press x Threaded Ends Available (Consult Factory)
Blow-Out Proof Stem
Conforms to MSS SP-110

*Not intended for use in potable water.

MATERIAL LIST

ITEM	PART	MATERIAL	ASTM SPEC	
1	Body	Bronze	B584	
2	End Cap	Bronze	B584	
3	Stem	Brass	B16	
		316 Stainless Steel (1)	A276	
4	Packing Nut	Brass	B16	
5	Packing	PTFE		
6	Thrust Washer	RPTFE, 25% Glass Filled		
7	Ball	CP Brass	B283	
		316 Stainless Steel (1)	A276	
8	Seat	RPTFE, 15% Glass Filled		
9	O'Ring	Viton	Commercial	
10	Handle	Steel w/Zinc Plating	Commercial	
11	Hand Grip	Vinyl	Commercial	
12	Handle Nut	Steel w/Zinc Plating	Commercial	
13	Bolt	Steel w/Zinc Plating	Commercial	
14	Nut	Steel w/Zinc Plating	Commercial	
15	Press Adapters	Brass Fitting w/EPDM O-Ring	B283	

With Press Ends

(1) Ball & Stem are stainless steel for 8603 P2


DIMENSIONS


	UNITS	1/2" DN15	3/4" DN20	1" DN25	1-1/4" DN32	1-1/2" DN40	2" DN50
A (DIA)	INCHES	0.50	0.75	1.00	1.25	1.50	2.00
A (DIA)	mm	13	19	25	32	38	51
STD INSERTION	INCHES	0.87	0.98	0.98	1.02	1.42	1.58
DEPTH	mm	22	25	25	26	36	40
В	INCHES	6.03	7.14	7.82	8.93	9.54	11.9
Ь	mm	153	181	199	227	242	302
н	INCHES	1.85	2.20	2.65	2.79	2.97	3.47
	mm	47	56	67	71	75	88
	INCHES	4.06	4.58	6.30	6.32	7.20	7.20
	mm	103	116	160	161	183	183
w	INCHES	1.95	2.19	2.48	3.00	3.13	3.78
VV	mm	50	56	63	76	80	96
F	THREAD	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
	SIZE	NPT	NPT	NPT	NPT	NPT	NPT
Cv	INCHES	17	31	60	110	185	360

Note: DN (Diameter Nominal) = Metric equivalent size.

+Non-Shock

Rev. 6





Press End Adapter (4151 SERIES)

The information presented on this sheet is correct at time of publication. Hammond Valve reserves the right to change design and/or materials without notice. For our Installation, Operation and Maintenance Manual and the most current product information go to www.hammondvalve.com. Hammond Valve is a registered trademark of Milwaukee Valve.

