



MATERIALS LIST			
ITEM	PART	MATERIALS	ASTM SPEC.
1	Body	Brass, Forged	B283, C37700
2	Tailpiece	Brass, Forged	B283, C37700
3	Ball	Brass	B124, C37700
		Chrome Plating	B456, SC1
4	Ball Seal	Teflon	PTFE
5	Stem	Brass	B124, C37700
6	O-Ring	Buna-	UL LISTED
7	Packing	Teflon	PTFE
8	Packing Nut	Brass	B124, C37700
9	Handle	Zinc	B86, AG40B
10	Screw	Steel/Zinc Plate	B633

AGENCY APPROVALS



DIMENSIONS			
DIMENSIONS	UNITS	1/2"	3/4"
A Ø	INCHES	0.39	0.591
	mm	10.0	15.0
B	INCHES	2.14	2.508
	mm	54.4	63.7
C	INCHES	1.07	1.256
	mm	27.3	31.9
D	INCHES	1.33	1.583
	mm	33.7	40.2
E	INCHES	1.36	1.36
	mm	34.6	34.6
F	THREAD	1/2"	3/4"
	NPT		

FEATURES

- FORGED ONE-PIECE BRASS
- STANDARD-PORT BALL VALVE

RATINGS MARKING

- 5G = 5 PSI
- 1/2" 150,000 BTU/HR
- 3/4" 400,000 BTU/HR
- MINIMUM FLOW CAPACITY
- INTERNATIONAL

The information presented on this sheet is correct at time of publication. Hammond Valve reserves the right to change design and/or materials without notice. For our Installation, Operation and Maintenance Manual and the most current product information go to www.hammondvalve.com. Hammond Valve is a registered trademark of Milwaukee Valve.

⚠ State of California Prop 65 **WARNING:** Cancer and Reproductive Harm. For more information visit www.p65warnings.ca.gov.

