
Bronze Gate Valve 300 SWP - 1000 WOG † Solid Wedge Disc • Non-Rising Stem Union Bonnet • Threaded Ends • Stainless Seat Conforms to: MSS SP-80

Wear-resistant stainless seat rings are securely expanded into the body to assure trouble-free service. Normal seating wear is restricted to the bronze wedge and can be easily replaced.



Note:	Not	intende	d for	use	in	potal	ble	water.
-------	-----	---------	-------	-----	----	-------	-----	--------

MATERIAL LIST							
No.	PART	MATERIAL	SPECIFICATION				
1	Body	Bronze	ASTM B61				
2	Bonnet	Bronze	ASTM B61				
3	Wedge Disc	Bronze	ASTM B61				
4	Stem	Bronze	ASTM B61				
5	Stuffing Box	Bronze	ASTM B61				
6	Union Bonnet Nut	Bronze	ASTM B61				
7	Seat Ring	St. Steel	ASTM A 240 TY304				
8	Packing	Graphite	Commercial				
9	Gland	Brass	ASTM B 124 C37700				
10	Packing Nut	Brass	ASTM B 283 C37700				
11	Handwheel	Mall. Iron	Commercial				
12	Handwheel Nut	Brass	Commercial				
13	Name Plate	Aluminum	Commercial				

DIMENS					
Units	Size	Α	В	С	C _v
Inches mm	1/4	1.81 46	4.13 105	2.00 51	5.6
Inches mm	3/8	1.88 48	4.13 105	2.00 51	10.7
Inches mm	1/2	2.25 57	4.31 110	2.50 64	17.6
Inches mm	3/4	2.50 64	4.56 116	2.75 70	32.0
Inches mm	1	3.00 76	5.19 132	2.75 70	54.0
Inches mm	1 1/4	3.38 86	5.94 151	3.44 87	97.0
Inches mm	1 1/2	3.50 89	6.38 162	3.75 95	135.0
Inches mm	2	3.75 95	7.69 195	4.25 108	230.0

† Non-Shock

The information presented on this sheet is correct at time of publication. Hammond Valve reserves the right to change design and/or materials without notice. For our Installation, Operation and Maintenance Manual and the most current product information go to www.hammondvalve.com. Hammond Valve is a registered trademark of Milwaukee Valve.

