

UP645 1/4"-2"

300 psig WOG †
Solid Wedge Disc • Non-Rising Stem
Threaded Bonnet • Threaded Ends
Dimensions and Workmanship Conform to MSS SP-80

Bronze Gate Valve For Potable Water



MATERIALS LIST


IVIA I ENIALS EIS I							
ITEM	PART	MATERIALS	ASTM SPEC.				
1	Body	Bronze	B584 C89833				
2	Bonnet	Bronze	B584 C89833				
3	Wedge	Bronze	B584 C89833				
4	Stem	Brass	B21 C46400, H02				
5	Stuff Nut	Brass	B283 C37700				
6	Check Nut	Brass	B283 C27450				
7	Gland ¹	Brass	B283 C37700				
8	Wheel Nut	Brass	Commercial				
9	Handwheel	Mall. Iron	Commercial				
10	Packing	Graphite	Commercial				
11	Name Plate	Sh. Alum	Commercial				

¹ Not used on 1/2" and smaller

DIMENSIONS

Units	Size	Α	В	С	Cv
INCHES	1/4	1.75	3.63	2.00	5.6
mm		44	92	51	
INCHES	3/8	1.81	3.63	2.00	10.7
mm		46	92	51	
INCHES	1/2	2.00	3.63	2.00	17.6
mm		51	92	51	
INCHES	3/4	2.18	4.38	2.50	32.0
mm		55	111	64	
INCHES	1	2.56	5.00	2.75	54.0
mm		65	127	70	
INCHES	1 1/4	2.78	5.31	3.44	97.0
mm		71	135	87	
INCHES	1 1/2	2.81	6.34	3.75	135.0
mm		71	161	95	
INCHES	2	3.31	7.44	3.75	230.0
mm		84	189	95	

[†] Non-Shock



Note: Lead free refers to the wetted surface of the pipe, fittings and fixtures in potable water systems that have a weighted average lead content ≤0.25%. Source: California Health and Safety Code (116875).

The information presented on this sheet is correct at time of publication. Hammond Valve reserves the right to change design and/or materials without notice. For our Installation, Operation and Maintenance Manual and the most current product information go to www.hammondvalve.com. Hammond Valve is a registered trademark of Milwaukee Valve.

