


Bronze Gate Valve for Potable Water 200 psig @ 250°F † Solid Wedge Disc • Non-Rising Stem **Threaded Bonnet • Press Ends Dimensions and Workmanship Conform to MSS SP-80**

MATERIALS LIST


ITEM	PART	MATERIALS ASTM SPEC.		
1	Body	Bronze	B584 C89833	
2	Bonnet	Bronze	B584 C89833	
3	Wedge	Bronze	B584 C89833	
4	Stem	Brass	B21 C46400, H02	
5	Stuff Nut	Brass	B283 C37700	
6	Check Nut	Brass	B283 C27450	
7	Gland ¹	Brass	B283 C37700	
8	Wheel Nut	Brass	Commercial	
9	Handwheel	Mall. Iron	Commercial	
10	Packing	Graphite	Commercial	
11	Name Plate	Sh. Alum	Commercial	
12	Press Adapters	Brass Fitting w/ EPDM O-Ring	C27450	

1 Not used on 1/2"

DIMENSIONS



Press End Adapter (4151 Series)



STD

		DEPTH			-	-
INCHES	1/2	.87	5.00	3.63	2.00	17.6
mm		22	127	92	51	
INCHES	3/4	.98	5.76	4.38	2.50	32.0
mm		25	146	111	64	
INCHES	1	.98	6.56	5.00	2.75	54.0
mm		25	167	127	70	
INCHES	1 1/4	1.02	6.85	5.31	3.44	97.0
mm		26	174	135	87	
INCHES	1 1/2	1.42	7.29	6.34	3.75	135.0
mm		36	185	161	95	
INCHES	2	1.58	9.31	7.44	3.75	230.0
mm		40	237	189	95	

В

† Non-Shock

*Both the valve and 4151 series press end adapters are tested and certified by IAPMO R & T to NSF/ANSI 61 and NSF/ANSI 372 for "Lead Free" compliance.

Note: Lead free refers to the wetted surface of the pipe, fittings and fixtures in potable water systems that have a weighted average lead content $\leq 0.25\%$. Source: California Health and Safety Code (116875).

The information presented on this sheet is correct at time of publication. Hammond Valve reserves the right to change design and/or materials without notice. For our Installation, Operation and Maintenance Manual and the most current product information go to www.hammondvalve.com. Hammond Valve is a registered trademark of Milwaukee Valve. A State of California Prop 65 WARNING: Cancer and Reproductive Harm. For more information visit www.p65warnings.ca.gov.

C

Cv



12

UP-25