



UP647 3/8"-2"



Bronze Gate Valve for Potable Water
300 psig WOG †
Solid Wedge Disc • Non-Rising Stem
Threaded Bonnet • Solder Ends

Dimensions and Workmanship Conform to MSS SP-80

MATERIALS LIST


ITEM	PART	MATERIALS	ASTM SPEC.
1	Body	Bronze	B584 C89833
2	Bonnet	Bronze	B584 C89833
3	Wedge	Bronze	B584 C89833
4	Stem	Brass	B21 C46400, H02
5	Stuff Nut	Brass	B283 C37700
6	Check Nut	Brass	B283 C27450
7	Gland ¹	Brass	B283 C37700
8	Wheel Nut	Brass	Commercial
9	Handwheel	Mall. Iron	Commercial
10	Packing	Graphite	Commercial
11	Name Plate	Sh. Alum	Commercial

1 Not used on 1/2" and smaller

DIMENSIONS

Units	Size	A	B	C	D	E	Cv
INCHES	3/8	1.63	3.56	2.00	0.88	0.38	10.7
mm		41	91	51	22	10	
INCHES	1/2	1.88	3.56	2.00	0.88	0.50	17.6
mm		48	91	51	22	13	
INCHES	3/4	2.50	4.75	2.50	1.00	0.75	32.0
mm		64	121	64	25	19	
INCHES	1	3.00	5.00	2.75	1.19	0.91	54.0
mm		76	127	70	30	23	
INCHES	1 1/4	3.25	5.88	3.44	1.31	0.97	97.0
mm		83	149	87	33	25	
INCHES	1 1/2	3.63	6.50	3.75	1.44	1.09	135.0
mm		92	165	95	37	28	
INCHES	2	4.31	7.44	3.75	1.63	1.34	230.0
mm		110	189	95	41	34	

† Non-Shock



Note: Lead free refers to the wetted surface of the pipe, fittings and fixtures in potable water systems that have a weighted average lead content ≤0.25%. Source: California Health and Safety Code (116875).

The information presented on this sheet is correct at time of publication. Hammond Valve reserves the right to change design and/or materials without notice. For our Installation, Operation and Maintenance Manual and the most current product information go to www.hammondvalve.com. Hammond Valve is a registered trademark of Milwaukee Valve.

⚠ State of California Prop 65 **WARNING:** Cancer and Reproductive Harm. For more information visit www.p65warnings.ca.gov.



HAMMONDVALVE