



UP8501/8503 P2* ½"-3"

Bronze Ball Valve For Potable Water Two Piece

Standard Port (1" - 3") Full Port (1/2" - 3/4") 200 psig @ 250°F†


Press x Press Ends


Press x Threaded Ends Available (Consult Factory)

Blow-Out Proof Stem


Dimensions and Workmanship Conform to MSS SP-110

MATERIAL LIST										
ITEM	PART	MATERIAL	ASTM SPEC							
1	Body	Cast Bronze	B584 C89833							
2	Tailpiece	Cast Bronze	B584 C89833							
3	Ball	Brass w/Hard Chrome Plating	B283 C27450							
	Dali	316 Stainless Steel (1)	A276 S31600							
4	Seat	RPTFE, 15% Glass filled								
5	Stem	Brass	B21 C46400 H02							
		316 Stainless Steel (1)	A276 S31600							
6	Thrust Washer	RPTFE, 25% Glass Filled								
7	Packing	PTFE								
8	Packing Nut	Brass	B16 C36000							
9	Handle	Steel w/Zinc Plating	Commercial							
10	Handle Grip	Vinyl	Commercial							
11	Handle Nut	Steel w/Zinc Plating	Commercial							
12	Press Adapters	Brass Fitting w/EPDM O-Ring (1/2" - 2")	B283 C27450							
		Copper (2 1/2" - 3")	B88							
13	O-Ring	EPDM								
14	Backing Seal	Acetal								
15	Backing Ring	304 Stainless Steel	A276							






Note: 2 1/2" & 3" are built from UP8511/UP8513 Valve





Press End Adapter (4151 Series)



DIMENSIONS

	UNITS	1/2" DN15	3/4" DN20	1" DN25	1-1/4" DN32	1-1/2" DN40	2" DN50	2-1/2" DN65	3" DN80
A (DIA)	INCHES	0.50	0.76	0.88	1.07	1.32	1.57	2.00	2.31
A (DIA)	mm	13	19	22	27	33	40	51	59
STD	INCHES	0.87	0.98	0.98	1.02	1.42	1.58	1.80	2.10
Insertion	mm	22	25	25	26	36	40	46	53
В	INCHES	5.19	6.17	7.17	7.57	8.44	10.30	12.02	13.94
	mm	132	157	182	192	214	262	305	354
	INCHES	1.91	2.32	2.68	2.82	3.00	3.36	3.47	3.88
D	mm	47	59	68	72	76	85	88	99
E	INCHES	3.82	4.55	4.56	6.33	6.33	7.19	7.19	7.19
	mm	94	116	116	161	161	183	183	183

Note: DN (Diameter Nominal)=Metric equivalent size.

†Non-Shock

*Both the valve and 4151 series press end adapters are tested and certified by IAPMO R & T to NSF/ANSI 61 and NSF/ANSI 372 for "Lead Free" compliance.

Note: Lead free refers to the wetted surface of the pipe, fittings and fixtures in potable water systems that have a weighted average lead content \leq 0.25%. Source: California Health and Safety Code (116875).

The information presented on this sheet is correct at time of publication. Hammond Valve reserves the right to change design and/or materials without notice. For our Installation, Operation and Maintenance Manual and the most current product information go to www.hammondvalve.com. Hammond Valve is a registered trademark of Milwaukee Valve.

